



CHAMPION OF ROUGH ROADS

BOXER *X150*
NOW WITH 5 GEARS



- HIGH POWER
- DURABLE
- COMFORTABLE
- LOW MAINTENANCE
- WIDER SEAT



X150



Available in 3 colours:



Red

Black

Blue

ENGINE

Engine Type	4 stroke, Air cooled, Single Cylinder, SOHC, Single Plug
Displacement (cc)	144.8 cc
Max. Power (Ps @ RPM)	12 PS @ 7500 rpm
Max. Torque (Nm @ RPM)	12.55 NM @ 5000 rpm
Transmission	5 Speed Constant Mesh (All down shift)

CHASSIS AND BODY

Frame Type	Tubular
Front Suspension	Hydraulic, Telescopic, 125 mm travel
Rear Suspension	Hydraulic Twin Suspension, SNS type, 100 mm travel
Wheel -Front & Rear	Alloy
Brakes - Front & Rear	Mechanically Expanding Shoes / Hydraulic Disc Brake
Brake Size - Front & Rear	130 mm Drum Brake / 240 mm Disc Brake
Tyre Front	3.00 - 17", 46P Semi Knobby
Tyre Rear	100/90 - 17", 55P Semi Knobby
Steering-cum-Ignition Lock	Yes
Starting	Kick & Electric Start
Tail Lamp	12V, 21/5W
Blinkers	10 W

FUEL TANK

Fuel Tank Capacity (ltrs)	11 ltrs
Usable Reserve (ltrs)	2.5 ltrs
Unusable Reserve (ltrs)	1 ltr

CONTROLS

Steering	Handlebar	
Accelerator	On Handlebar, RH Grip	
Gears	Left Foot, Pedal Operated	
Brakes	Front Rear	Drum-130 mm Drum-130 mm

ELECTRICALS

System	12V, DC
Battery	12V 4Ah VRLA
Headlamp	12V 35/35W HS1

DIMENSIONS

Wheel Base (mm)	1285
Length (mm)	2016
Height (mm)	1134
Width (mm)	740
Ground Clearance (mm)	190
Kerb Weight (Kg)	125

**For any enquiries
please call on
XXXXX**

Dealer stamp & address

- Accessories shown may not be part of the standard fitment
- Values given above are nominal & for guidance only, 15% variation is allowed to cater for production & measurement
- All dimensions are under un-laden conditions
- Definitions of terminologies wherever applicable are as per relevant IS/ISO standards
- Specifications are subject to change without notice



CHAMPION OF ROUGH ROADS

BOXER *X 150*
NOW WITH 5 GEARS



HIGH POWER



DURABLE



COMFORTABLE



LOW MAINTENANCE



WIDER SEAT



X150



Available in 3 colours:



ENGINE	
Engine Type	4 stroke, Air cooled, Single Cylinder, SOHC, Single Plug
Displacement (cc)	144.8 cc
Max. Power (Ps @ RPM)	12 PS @ 7500 rpm
Max. Torque (Nm @ RPM)	12.55 NM @ 5000 rpm
Transmission	5 Speed Constant Mesh (All down shift)

CHASSIS AND BODY	
Frame Type	Tubular
Front Suspension	Hydraulic, Telescopic, 125 mm travel
Rear Suspension	Hydraulic Twin Suspension, SNS type, 100 mm travel
Wheel -Front & Rear	Alloy
Brakes - Front & Rear	Mechanically Expanding Shoes / Hydraulic Disc Brake
Brake Size - Front & Rear	130 mm Drum Brake / 240 mm Disc Brake
Tyre Front	3.00 - 17", 46P Semi Knobby
Tyre Rear	100/90 - 17", 55P Semi Knobby
Steering-cum-Ignition Lock	Yes
Starting	Kick & Electric Start
Tail Lamp	12V, 21/5W
Blinkers	10 W

FUEL TANK	
Fuel Tank Capacity (ltrs)	11 ltrs
Usable Reserve (ltrs)	2.5 ltrs
Unusable Reserve (ltrs)	1 ltr

CONTROLS		
Steering		Handlebar
Accelerator		On Handlebar, RH Grip
Gears		Left Foot, Pedal Operated
Brakes	Front	Drum-130 mm
	Rear	Drum-130 mm

ELECTRICALS	
System	12V, DC
Battery	12V 4Ah VRLA
Headlamp	12V 35/35W HS1

DIMENSIONS	
Wheel Base (mm)	1285
Length (mm)	2016
Height (mm)	1134
Width (mm)	740
Ground Clearance (mm)	190
Kerb Weight (Kg)	125

**For any enquiries
please call on
XXXXX**

Dealer stamp & address

- Accessories shown may not be part of the standard fitment
- Values given above are nominal & for guidance only, 15% variation is allowed to cater for production & measurement
- All dimensions are under un-laden conditions
- Definitions of terminologies wherever applicable are as per relevant IS/ISO standards
- Specifications are subject to change without notice