

THE ALL NEW
pulsar
NS200



UPDATED CONSOLE



USD FORKS



DUAL CHANNEL ABS

BSVI
LATEST BSG COMPLIANT



SOLE DISTRIBUTOR FOR NEPAL
Hansraj Hulaschand & Co Pvt. Ltd.
Teku Road, Kathmandu, Ph. No: 5330001/5368088
url: nepal.globalbajaj.com/en

[/PulsarNepal](#)

[/PulsarNepal](#)

[/Company/Golchhagroup](#)



THE ALL NEW
NS SHARPER
THAN EVER
WITH USD FORKS AND DUAL CHANNEL ABS



THE ALL NEW
pulsar
NS200

THE ALL NEW
pulsar
NS160





SPECIFICATIONS

PARAMETER	SPECIFICATION	PULSAR NS 200	PULSAR NS 160
ENGINE	Type	Liquid-cooled, Triple Spark, 4-valve, Fuel Injection, DTS-i, BS6 Engine	Oil-cooled, Twin Spark, 4-valve, Fuel Injection, DTS-i, BS6 Engine
	Displacement	199.5 cc	160.3 cc
	Max.Power	18 kW [24.5 PS]@ 9750 rpm	12.5 kW [17 PS]@ 9000 rpm
	Max.Torque	18.74 Nm@ 8000 rpm	14.6 Nm@ 7250 rpm
GEARBOX		6 speed constant mesh	5 speed constant mesh
BRAKES	Front	Dual Channel ABS, 300 mm Disc	
	Rear	230 mm Disc (ABS)	
SUSPENSION	Front	Upside Down Forks	
	Rear	Nitrox mono shock absorber with canister	
TYRES	Front	100/80 -17 52 P Tubeless	
	Rear	130/70-17 62 P Tubeless	
DIMENSIONS	Length	2017 mm	
	Width	804 mm	
	Height	1075 mm	1060 mm
	Ground Clearance	169 mm	170 mm
	Wheelbase	1363 mm	1372 mm
	Kerb weight	158 kg	152 kg
	Fuel tank capacity	12 L	
ELECTRICALS	Console features	Gear position indicator, Distance-to-empty indicator	
	Headlamp	High Beam 12 V 60 W, H4 Low Beam 12 V 55 W	High Beam 12 V 35 W Low Beam 12 V 35 W
	System	DC, 12 V 8 Ah VRLA Battery	DC, 12 V 4 Ah VRLA Battery